

# Unvented Indirect Commercial Calorifier Range



- Floor Standing Indirect Unvented Calorifiers.(450 - 4000L)
- Stainless Steel tank.
- All tanks pressure tested to 8bar. Higher pressures are available to order.
- Unique coil design to enhance heat transfer and recovery.
- Multiple coil options available.
- Ergonomically designed with all electrical and plumbing connections within easy Installation access.
- Factory fitted Temperature and Pressure relief valve.
- Unvented control kits available if required.
- Highly efficient yet environmentally friendly tank insulation housed within an attractive outer casing.
- BBA, CE & WRAS approved.
- Grey Plastosol outer case finish as standard.
- Vented options available.
- Domestic units available 80 - 305L

## Performance

Nominal Capacity Litres	Height	Diameter	Connections Cold / Hot	Standard Coil Rating kW	Coil Connections	Optional Coil Rating kW
450	1624	750	1"/1"	27	28mm	54-216
500	1722	750	1"/1"	27	28mm	54-216
680	2292	750	1"/1"	27	28mm	54-216
840	2776	750	1.5"/ 1.5"	54	28mm	54-216
965	1800	990	1.5"/ 1.5"	54	28mm	54-216
1125	2050	990	1.5"/ 1.5"	54	28mm	54-216
1380	2074	1090	1.5"/ 1.5"	54	28mm	54-216
1775	2574	1090	1.5"/ 1.5"	54	28mm	54-216
1875	2038	1290	2" / 2"	54	28mm	54-216
2155	2288	1290	2" / 2"	54	28mm	54-216

MHG Heating Ltd Unit 4 Epsom Downs Metro Centre, Waterfield, Tadworth, Surrey. KT20 5LR  
 Phone 08456 448802 Fax 08456 448803 Email [info@mhgheating.co.uk](mailto:info@mhgheating.co.uk) web [www.mhgheating.co.uk](http://www.mhgheating.co.uk)

