

# Unvented Direct Calorifier Range. 90-500L



- Floor Standing Direct Unvented Calorifiers.(90 -500L)
- Stainless Steel tank.
- All tanks pressure tested to 25bar.
- Ergonomically designed with all electrical and plumbing connections within easy Installation access.
- Integrated twin 3 kW Immersion heater with control and limit thermostats.
- Factory fitted Temperature and Pressure relief valve.
- Unvented control kit supplied as standard.
- Lifetime manufactures tank guarantee.
- 3 Year electrical component guarantee.
- Inlet and Outlet connections fitted with BSP fittings to ease installation. ( $3/4" \leq 300L / 1" \geq 400L$ )
- Highly efficient yet environmentally friendly tank insulation housed within an attractive outer casing.
- BBA, CE & WRAS approved.
- Vented options available.
- Commercial units available 600-100,000L

## Performance

Nominal Capacity Litres	Height / Diameter	Height To Cold Inlet	Height to Secondary Return	Heat Up Time mins	Reheat Time following 70% draw mins	Heat loss in kW/24 hrs
90	750 / 510	170	~	52	27	1.63
125	935 / 510	170	~	72	37	1.70
150	1060 / 510	170	~	86	45	1.92
170	1200 / 510	170	~	98	51	2.04
200	1120 / 554	195	815	108	63	2.45
250	1330 / 554	195	975	144	75	2.69
300	1650 / 554	195	1255	202	136	2.71
400	1590 / 660	240	1240	242	198	2.94
500	1835 / 660	240	1390	289	236	3.15

MHG Heating Ltd Unit 4 Epsom Downs Metro Centre, Waterfield, Tadworth, Surrey. KT20 5LR  
 Phone 08456 448802 Fax 08456 448803 Email [info@mhgheating.co.uk](mailto:info@mhgheating.co.uk) web [www.mhgheating.co.uk](http://www.mhgheating.co.uk)

