

Unvented Indirect Calorifier Range. 600-1000L



- Floor Standing Indirect Unvented Calorifiers.(600-1,000L)
- Stainless Steel tank.
- All tanks pressure tested to 25bar.
- Unique coil design to enhance heat transfer and recovery.
- Ergonomically designed with all electrical and plumbing connections within easy Installation access.
- Integrated 3 kW Immersion heater with control and limit thermostats.
- Factory fitted Temperature and Pressure relief valve.
- Unvented control kit supplied as standard.
- Lifetime manufactures tank guarantee.
- 3 Year electrical component guarantee.
- Inlet, Outlet, Flow and Return connections fitted with 1" BSP fittings to ease installation.
- Highly efficient yet environmentally friendly tank insulation housed within an attractive outer casing.
- BBA, CE & WRAS approved.
- Vented options available.
- Commercial units available 2,000-100,000L
- Higher recovery units available.

Nominal Capacity Litres	Height / Diameter	Height to Cold Inlet	Height to Secondary Return	Standard Heat Up Time Minutes	Standard Reheat Time following 75% draw Minutes	Coil Rating kW Standard / Hi	Heat loss in kW/24 hrs	Presseure Vessel Size
600	1435 / 822	280	1170	69	34	25 / 41	2.04	50L
700	1664 / 822	280	1370	72	36	28 / 48	2.45	100L
800	1864 / 822	280	1580	74	38	31 / 52	2.69	100L
900	2064 / 822	280	1780	78	35	33 / 60	2.71	100L
1000	2314 / 822	280	2180	86	37	33 / 70	2.94	100L

MHG Heating Ltd Unit 4 Epsom Downs Metro Centre, Waterfield, Tadworth, Surrey. KT20 5LR
 Phone 08456 448802 Fax 08456 448803 Email info@mhgheating.co.uk web www.mhgheating.co.uk



Unvented Indirect Twin Coil Calorifier Range

600-1000L



- Floor Standing Indirect Unvented Twin Coil Calorifiers. (600-1,000L)
- Stainless Steel tank rated to 25 bar.
- Unique coil design to enhance heat transfer and recovery.
- Ergonomically designed with all electrical and plumbing connections within easy installation access.
- Integrated 3 kW Immersion heaters with control and limit thermostats.
- Factory fitted Temperature and Pressure relief valve.
- Unvented control kit supplied as standard.
- Lifetime manufactures tank guarantee.
- 3 Year electrical component guarantee.
- Inlet, Outlet Flow and Return connections fitted with 1" BSP fittings to ease installation.
- Highly efficient yet environmentally friendly tank insulation housed within an attractive outer casing.
- BBA, CE & WRAS approved.
- Treble Coil units available.
- Vented options available.
- Commercial units available 2,000-100,000L

Nominal Capacity Litres	Height / Diameter	Height to Cold Inlet	Height to Secondary Return	Standard Heat Up Time Minutes	Standard Reheat Time following 75% draw Minutes	Coil Rating Lower / Upper	Heat loss in kW/24 hrs	Presseure Vessel Size
600	1435 / 822	280	1170	69	34	25 / 25	2.04	50L
700	1664 / 822	280	1370	72	36	28 / 28	2.45	100L
800	1864 / 822	280	1580	74	38	31 / 31	2.69	100L
900	2064 / 822	280	1780	78	35	33 / 33	2.71	100L
1000	2314 / 822	280	2180	86	37	33 / 33	2.94	100L

MHG Heating Ltd Unit 4 Epsom Downs Metro Centre, Waterfield, Tadworth, Surrey. KT20 5LR
 Phone 08456 448802 Fax 08456 448803 Email info@mhgheating.co.uk web www.mhgheating.co.uk

